



PRESENT VIEW AND PERSPECTIVES IN THE OPTIMIZATION OF ELECTRICAL PARAMETERS OF WIRELESS COMMUNICATION SYSTEM

Iulian PANAIT, Emanuel BUICĂ

Valahia University of Targoviste, Doctoral School of Engineering

E-mail: ipanait1@mapn.ro

Abstract. *The paper aims to analyze the performance of wireless communication systems by focusing on key electrical parameters such as signal power, bandwidth, signal-to-noise ratio (SNR), attenuation, and modulation techniques. The study utilizes advanced concepts including MIMO (Multiple Input Multiple Output) systems, dynamic power control, and Shannon-Hartley theorem, all analyzed using MATLAB/Octave for simulation and optimization purposes. The investigation is conducted to optimize the efficiency and reliability of wireless networks, ensuring better resource management and improved quality of service (QoS).*

Keywords: wireless communication, signal power, bandwidth, SNR, attenuation, modulation, MIMO, MATLAB, Octave, IA, blockchain, multiplexing, dynamic access, beamforming.

1. INTRODUCTION

The wireless systems represent the backbone of modern communications, being fundamental for a wide range of applications, from mobile telephony and data networks to the Internet of Things (IoT) and satellite communications [1]. The development, structure, and operation of these systems are governed by a series of essential electrical parameters, which include signal power, bandwidth, signal-to-noise ratio (SNR), attenuation, and modulation [2]. Each of these parameters plays a critical role in determining the performance of wireless networks, directly influencing transmission capacity, energy consumption, and the quality of service provided to users [3]. Understanding and optimizing these parameters through analytical methods and precise mathematical calculations are essential for the efficient design and operation of these networks, especially in the context of increasing demands for bandwidth and global connectivity [4]. As wireless technology continues to evolve, addressing these parameters in an integrated and complex manner becomes imperative to ensure the performance and sustainability of future communication systems [5].

2. CURRENT DEVELOPMENT OF WIRELESS SYSTEMS

The current development of wireless systems represents an essential aspect of technological progress in recent decades, profoundly influencing various fields, from communications and health to industrial automation and entertainment [6]. Wireless systems, once viewed as avant-garde innovations, have now become an integral part of daily life, with an omnipresent presence in homes,

public spaces, offices, and even vehicles [7]. This rapid evolution can be attributed to significant advances in communication technologies such as 5G standards, Wi-Fi 6, and more recently, research into 6G [8]. These new generations of wireless technologies promise higher data transfer speeds, extremely low latencies, and greatly improved connectivity capacity, allowing an ever-increasing number of devices to be interconnected simultaneously without compromising service quality [1]. Besides performance improvements, the development of wireless systems has also been marked by an expansion of application domains [6]. Wireless technologies are no longer limited to simple data transmission but have become critical infrastructures for the Internet of Things (IoT), which includes a vast range of connected devices, from smart appliances and security systems to industrial equipment and portable medical devices [3]. This integration of wireless technologies into IoT has stimulated the development of complex and robust networks capable of managing a massive flow of real-time information [8]. At the same time, the security of these systems has become a central concern, as cyber-attacks can have devastating consequences in a context where so many aspects of our lives are interconnected and remotely controlled.

In parallel, the increasing demands for bandwidth and higher speeds have led to the development of new technologies and strategies for managing the radio spectrum [4]. Since the radio spectrum is a limited and extremely valuable resource, companies and regulatory authorities are working together to optimize its use by developing technologies such as multiplexing and efficient utilization of available frequencies [9]. Additionally, new technologies like Li-Fi have emerged, which use visible light to transmit data, thus offering an alternative to traditional radio frequency networks with potential advantages in certain use scenarios, such as highly secure environments or inside buildings where radio interference is a problem.

The social impact of the development of wireless systems cannot be underestimated [2]. The expansion of wireless network coverage has contributed to reducing the digital divide by providing internet access and educational resources to isolated and disadvantaged communities [6]. At the same time, the evolution of these technologies has generated a series of new challenges, such as concerns related to privacy, dependence on mobile devices, and the impact of electromagnetic radiation on health [5]. These challenges require a concerted effort from industry, governments, and civil society to develop policies and regulations that balance technological benefits with the

protection of users' rights and health [7]. Another important aspect of the current development of wireless systems is their interaction with other emerging technologies, such as artificial intelligence (AI) and blockchain [1]. AI is increasingly used to optimize wireless networks by applying machine learning algorithms for efficient data traffic management and anticipating user requirements [8]. At the same time, blockchain technologies are being explored to ensure the security and integrity of data transmitted through wireless networks, offering solutions to problems related to authentication, privacy, and resilience to cyber-attacks [3].

3. STRUCTURE AND OPERATION OF WIRELESS SYSTEMS

The structure and operation of wireless systems are fundamental elements in understanding how these technologies have revolutionized communications and have become essential for a wide range of applications, from mobile telephony to the Internet of Things (IoT) and satellite communications [5]. Wireless systems operate on the principle of transmitting data through electromagnetic waves, which can include radio frequencies, microwaves, infrared, or even visible light in the case of technologies like Li-Fi [2]. The structure of a wireless system involves several key components that work together to enable wireless communication [3]. These include transmitters, which are responsible for generating and transmitting signals, and receivers, which capture these signals and decode them into usable information [7]. Between the transmitter and receiver is the transmission medium, which in wireless systems is the air or, in some cases, the vacuum, as in space communications [9]. Each of these components plays a crucial role in ensuring an efficient and reliable data flow [1].

An essential aspect of the structure of wireless systems is the use of antennas, which are specialized devices for transmitting and receiving electromagnetic waves [6]. Antennas can vary in size and shape depending on the specific application and the signal frequency [8]. For example, in mobile telephony systems, antennas are integrated into mobile devices and base stations, which are strategically placed to ensure optimal signal coverage [4]. In Wi-Fi networks, antennas are integrated into routers and other network devices to provide connectivity in a localized space, such as a home or office [7]. In satellite communications, parabolic antennas are used to focus radio waves to and from satellites, which orbit the Earth at high altitudes [3]. The efficient operation of these antennas is essential for ensuring signal quality and data transmission speed [9].

In addition to antennas, another important structural element of wireless systems is the communication protocol, which defines the rules and standards for data transmission [1]. These protocols are essential for

ensuring interoperability between different devices and networks [2]. For example, Wi-Fi standards are regulated by the IEEE (Institute of Electrical and Electronics Engineers), and mobile telephony standards by international organizations such as 3GPP (3rd Generation Partnership Project) [4]. These standards establish essential parameters, such as bandwidth, modulation mode, and coding schemes, which directly influence the speed and reliability of data transmission [6]. The operation of wireless systems also depends on the management of the radio spectrum, a limited resource that must be used efficiently to avoid interference and ensure the quality of service [8]. The distribution of the radio spectrum is regulated at national and international levels, and recent innovations in its management include techniques such as dynamic spectrum access and multiplexing to optimize the use of available frequencies [5].

Another central aspect of the operation of wireless systems is the concept of a cell in mobile telephony networks [3]. Cellular networks are structured in a manner that divides the coverage area into cells, each served by a base station [7]. This structure allows for the reuse of frequencies in non-adjacent cells, thus maximizing spectrum efficiency [1]. As users move, their devices automatically connect to the nearest base station, a process known as handoff or handover, thereby ensuring continuity of service without interruptions [4]. Modern networks, such as 5G, use advanced techniques like beamforming and MIMO (Multiple Input Multiple Output) to improve capacity and coverage, allowing for faster and more efficient data transmission in dense environments like crowded cities [9].

In addition to hardware components and communication protocols, software also plays a critical role in the operation of wireless systems [8]. Power control, network management, and security algorithms are essential for optimizing performance and ensuring the reliability of wireless communications [6]. For example, in mobile networks, power control algorithms automatically adjust the power level of the signal emitted by a device to save energy and reduce interference with other devices on the network [2]. Also, security software is crucial for protecting data transmitted through wireless networks, which are vulnerable to interception and cyber-attacks [5]. Encryption and authentication protocols, such as WPA3 for Wi-Fi networks, are used to protect the confidentiality and integrity of data [7].

4. ELECTRICAL PARAMETERS OF WIRELESS SYSTEMS

The electrical parameters of wireless systems play a crucial role in determining the performance and efficiency of these technologies, having a direct impact on transmission capacity, energy consumption, and signal quality [3]. One of the most fundamental electrical

parameters in wireless systems is the signal power, which is often measured in decibels milliwatts (dBm) [7]. The power of the signal transmitted by a wireless emitter is calculated according to the relationship 1 [2].

$$P_{tx} = 10 \cdot \log_{10} \left(\frac{P}{1mW} \right) \quad (1)$$

Where it is the power in dBm, and P is the effective power in milliwatts [4]. For example, a power of 1 mW corresponds to a value of 0 dBm [2], while a power of 100 mW corresponds to a value of 20 dBm [7]. In communication systems, it is essential to optimize the signal power to ensure a balance between network coverage and energy consumption [9], especially in the case of mobile devices, where energy efficiency is critical [1].

Another essential parameter is the bandwidth of the signal, which defines the range of frequencies used for data transmission and is directly proportional to the information transfer rate [3]. Bandwidth is determined by calculating the difference between the maximum frequency and the minimum frequency of the signal and is expressed in hertz (Hz) [7]. In modern wireless systems, bandwidth can range from a few kilohertz (kHz) in the case of voice communications to hundreds of megahertz (MHz) or even gigahertz (GHz) in the case of 5G networks, which require large bandwidths to support very high transfer speeds [1]. The formula for calculating the transfer rate R of a communication channel can be expressed by the Shannon-Hartley theorem 2.

$$R = B \cdot \log_2 \left(1 + \frac{S}{N} \right) \quad (2)$$

Where B is the bandwidth of the channel [3], S is the signal power [7], and N is the noise power [1]. This formula shows that the maximum transfer rate is directly dependent on the bandwidth and the signal-to-noise ratio (SNR), which is another critical parameter in evaluating the performance of a wireless system [4]. The signal-to-noise ratio (SNR) is a measure of the quality of the received signal and is defined by the relationship 3.

$$SNR = \frac{P_{\text{signal}}}{P_{\text{noise}}} \quad (3)$$

Where it is the power of the useful signal, and P_noise is the power of the background noise [3]. The SNR is usually expressed in decibels (dB) and is calculated using the formula 4 [7].

$$SNR_{dB} = 10 \cdot \log_{10} \left(\frac{P_{\text{signal}}}{P_{\text{noise}} \text{ antat}} \right) \quad (4)$$

A higher SNR indicates better signal quality and, implicitly, more reliable data transmission [4]. For example, an SNR of 10 dB suggests that the signal is 10 times stronger than the noise, while an SNR of 20 dB indicates a signal 100 times stronger than the noise [7]. In practice, the SNR affects the modulation and coding

scheme used by the wireless system, influencing the Bit Error Rate (BER) and, implicitly, the quality of the service provided [3].

In addition to these parameters, signal attenuation is another essential aspect in wireless systems, described by the inverse square law, which states that the received signal power decreases proportionally with the square of the distance from the transmitter [2]. Signal attenuation L can be calculated using the formula 5 [6],

$$L(dB) = 20 \cdot \log_{10}(d) + 20 \cdot \log_{10}(f) + 20 \cdot \log_{10} \left(\frac{4\pi}{c} \right) \quad (5)$$

Where d is the distance between the transmitter and receiver, f is the signal frequency, and c is the speed of light [3]. This formula emphasizes the importance of frequency and distance in determining attenuation [7], which explains why higher frequency signals, such as those used in 5G networks, have a reduced geographical coverage [9] and require a higher density of base stations [1].

Another crucial parameter is the attenuation coefficient of the transmission medium, which varies depending on the materials through which the signal passes and the atmospheric conditions [5]. For example, radio signals can be significantly attenuated by physical obstacles such as buildings or trees and can be affected by atmospheric phenomena such as rain or fog [8]. This attenuation must be taken into account in the design and implementation of wireless networks, especially in dense urban environments where interference and obstacles are ubiquitous [3].

Another important aspect of the electrical parameters of wireless systems is signal modulation, which represents the process by which digital information is embedded into an analog carrier signal [7]. There are several modulation techniques used in wireless communications, including amplitude modulation (AM), frequency modulation (FM), and phase modulation (PM) [2]. For example, in the case of amplitude modulation (AM), the carrier signal S(t) can be expressed by the formula 6 [9].

$$S(t) = [1 + m(t)] \cdot \cos(2\pi f_c t) \quad (6)$$

Where m(t) is the modulation signal and It is the carrier frequency [5]. Depending on the type of modulation used [3], the performance of the wireless system can vary significantly in terms of the required bandwidth [7], signal strength [1], and resistance to interference [9].

5. DISCUSSIONS ON THE ANALYSIS AND OPTIMIZATION OF THE ELECTRICAL PARAMETERS OF WIRELESS SYSTEMS

The analysis and optimization of electrical parameters in wireless systems represent an essential domain in telecommunications engineering, having a direct impact

on the efficiency, capacity, and reliability of communication networks [5]. The optimization process begins with a detailed analysis of parameters such as signal power, bandwidth, signal-to-noise ratio (SNR), attenuation, and modulation, each of these being essential for ensuring optimal performance [2]. A critical aspect of the analysis is understanding the mathematical relationships that govern these parameters, as well as their impact on the quality of service provided by wireless systems [8]. For example, to optimize the signal power in a wireless network, it is essential to consider the formula 7 for calculating power in dBm [7].

$$P_{tx} = 10 \cdot \log_{10} \left(\frac{P}{1mW} \right) \quad (7)$$

Where optimization may involve reducing power losses along the path between transmitter and receiver, either by using more efficient antennas or by minimizing obstacles that cause attenuation.

Another fundamental aspect in the analysis and optimization of wireless systems is bandwidth management, which is closely related to the data transfer rate and spectral efficiency of the network. Shannon-Hartley formula 8.

$$R = B \cdot \log_2 \left(1 + \frac{S}{N} \right) \quad (8)$$

Which illustrates how the maximum transfer rate R depends on the bandwidth B and the signal-to-noise ratio. Optimizing these parameters involves not only expanding the bandwidth, but also improving the SNR by reducing the background noise N or by amplifying the useful signal S. For example, a common approach to improve the SNR in wireless networks is to use MIMO (Multiple Input Multiple Output), which allow the simultaneous transmission and reception of several data streams on different channels, thus increasing spectral efficiency and network capacity. The specific calculation for SNR in a MIMO system can be expressed by the formula 9.

$$SNR_{MIMO} = \frac{P_t \cdot \|H\|^2}{N_0 \cdot B} \quad (9)$$

Where H is the channel matrix and N_0 is the noise power spectral density. This formula shows how performance can be improved by optimizing the characteristics of the H transmission channel and by efficiently managing spectral resources.

Signal attenuation is another critical parameter that requires careful analysis and optimization. Attenuation can be caused by multiple factors, including the distance between the transmitter and receiver, physical obstacles, and atmospheric conditions. The general formula for calculating free-space attenuation is formula 10.

$$L(dB) = 20 \cdot \log_{10}(d) + 20 \cdot \log_{10}(f) + 20 \cdot \log_{10} \left(\frac{4\pi}{c} \right) \quad (10)$$

Where d is the distance, f is the frequency of the signal, and c is the speed of light. Optimizing this attenuation may involve adjusting the signal frequency, reducing the transmission distance by using additional base stations, or implementing advanced technologies such as beamforming, which directs the signal to the intended receiver to minimize loss. It is also essential to consider the effects of fading and multipath interference, which can lead to fluctuations in signal strength. In this context, techniques such as spatial diversity and the use of error correcting codes (FEC) can be used to compensate for these effects and optimize network performance.

Signal modulation is another critical area in the analysis and optimization of wireless systems because it determines how information is incorporated into the carrier signal. Optimizing the modulation technique involves choosing a scheme that provides an optimal balance between required bandwidth, signal strength, and robustness to noise. For example, advanced modulations such as QAM (Quadrature Amplitude Modulation) can provide high transfer rates, but require a higher SNR to operate efficiently, making them more susceptible to noise and interference. The general formula for signal strength in a QAM system is:

$$P_{QAM} = \frac{E_b \cdot R_s}{\log_2(M)} \quad (11)$$

Where E_b is the energy per bit, R_s is the symbol rate, and M is the number of modulation levels. Optimizing the parameters of this system may involve adjusting the number of M levels to find a compromise between transfer rate and noise immunity.

Another essential dimension in the optimization of wireless systems is energy consumption, especially in the case of mobile devices or wireless sensor networks, where battery life is critical. Optimizing power consumption involves strategies such as dynamic power control, where the transmitted power P_{tx} is adjusted based on distance to the receiver and channel conditions to minimize consumption without compromising signal quality. A relevant formula in this context is:

$$P_{tx,opt} = \frac{SNR_{min} \cdot N_0 \cdot B}{\|H\|^2} \quad (12)$$

Where SNR_{min} is the minimum signal-to-noise ratio required to maintain acceptable transmission quality. This calculation highlights the importance of dynamic power adjustment to balance network performance with energy requirements, especially in resource-constrained environments.

6. CONCLUSIONS

As demands for bandwidth, transmission speeds, and low power consumption continue to increase, wireless network engineers and designers must focus on continuous innovation and refinement of these

parameters. Optimization strategies such as the use of MIMO technologies, dynamic power control, efficient spectrum management and the implementation of advanced modulation techniques are essential to meet these requirements.

In an ever-evolving technological context, where wireless networks are becoming increasingly dense and complex, detailed analysis and optimization of electrical parameters become crucial to ensure robust and efficient connectivity. Thus, investment in research and development, along with a deep understanding of the theoretical and practical aspects of these parameters, will continue to be vital to support the continued growth and evolution of wireless communications globally.

7. REFERENCES

- [1] Fettweis, G., & Alamouti, S. (2014). 5G: Personal mobile internet beyond what cellular did to telephony. *IEEE Communications Magazine*, 52(2), 140-145.
- [2] Andrews, J.G., Buzzi, S., Choi, W., Hanly, S.V., Lozano, A., Soong, A.C.K., & Zhang, J.C. (2014). What will 5G be?. *IEEE Journal on Selected Areas in Communications*, 32(6), 1065-1082.
- [3] Tse, D., & Viswanath, P. (2005). *Fundamentals of Wireless Communication*. Cambridge University Press.
- [4] Goldsmith, A. (2005). *Wireless Communications*. Cambridge University Press.
- [5] Zhang, R., Zhang, R., Wang, K., & Zhang, Y. (2019). Energy-efficient hybrid analog and digital precoding design for millimeter-wave MIMO systems. *IEEE Transactions on Communications*, 67(4), 2678-2692.
- [6] Rappaport, T.S., Xing, Y., MacCartney, G.R., Molisch, A.F., Mellios, E., & Zhang, J. (2017). Overview of millimeter wave communications for fifth-generation (5G) wireless networks—with a focus on propagation models. *IEEE Transactions on Antennas and Propagation*, 65(12), 6213-6230.
- [7] Bi, S., Ho, C.K., & Zhang, R. (2015). Wireless powered communication: opportunities and challenges. *IEEE Communications Magazine*, 53(4), 117-125.
- [8] Zhu, H., Wang, J., Tang, D., & Li, G. (2016). Wireless power transfer with optimal power and beamforming control in wireless networks. *IEEE Transactions on Wireless Communications*, 15(6), 4024-4037.
- [9] Zhang, X., Molisch, A., Kung, S.Y., & Zhang, J. (2005). Variable-phase-shift-based RF-baseband codesign for MIMO antenna selection. *IEEE Transactions on Signal Processing*, 53(11), 4091-4103.